

# Low-Light 3G-SDI / HD-SDI



## WAT-2200

### SPECIFICATIONS

Model		WAT-2200
Pick-up element		1/2.8-inch CMOS image sensor
Number of total pixels		1952(H) x 1236(V)
Number of effective pixels		1080i/1080p: 1920(H) x 1080(V) / 720p: 1280(H) x 720(V)
Unit cell size		2.8μm x 2.8μm
Imaging system		RGB+W array mosaic filters on chip
Synchronizing system		Internal
Scanning system		Progressive
Video output		3G-SDI / HD-SDI (SMPTE292M)
Output format	3G-SDI	1080p60, 1080p50, 1080p59.94
	HD-SDI	1080i60, 1080i50, 1080i59.94, 1080p30, 1080p25, 1080p29.97, 720p60, 720p50, 720p59.94
Minimum illumination		0.1 lx. F1.2
Function settings		OSD(On Screen Display) operated by remote controller / RS-232(Compatible)
AE mode		AUTO / MANUAL
Shutter speed		OFF, 1/100, 1/120, 1/200, 1/500, 1/1000, 1/2000, 1/5000, 1/10000 sec.
Flickerless mode		ON / OFF
AGC		HIGH / MEDIUM / LOW
MGC		0 - 54dB
White balance		ATW / PWB / Preset
Noise reduction		2DNR ON / OFF
Privacy mask		16 areas
Mirror image		OFF / ON (H-FLIP, V-FLIP)
Back light compensation		ON / OFF
Defog		ON / OFF
White blemish correction		1023 pixels
Lens iris		DC
Power supply		+12V
Power consumption		2.22W (185mA)
Operating temperature		-10°C ~ +50°C
Storage temperature		-30°C ~ +70°C
Operating/Storage humidity		95%RH or less (Without condensation)
Lens mount		CS mount (Back focus adjustable)
Weight		135g

※Design and specifications are subject to change without notice.

### DIMENSIONS (mm)

